

## VIATOR® Bluetooth® Interface

010041 for use with HART field devices

The **VIATOR Bluetooth Interface** is a point-to-point HART PC modem for temporary connection to HART field devices that is used with software primarily as a configuration management tool. The modem can operate approximately 20 hours powered by replaceable AAA battery cells. The modem physically attaches to the HART field device with 18" leads and mini-grabber clips. The PC host uses internal **Bluetooth** interface or a USB to **Bluetooth** converter to communicate with the **Bluetooth** modem.



Pairing with host PCs, Pocket PCs and PDAs is simple. Default operating mode is to establish the connection with Windows **Bluetooth** serial port profile. Faceplate push button manually controls on/of and battery check mode. Faceplate LED displays communication heartbeat and battery charge remaining.

VIATORCheckBT™ PC software allows users to test connection with devices and to remotely turn off the modem, check battery charge remaining, put it to sleep to save battery, wake up from sleep when ready to continue use, and to remotely cause the LED to flash rapidly to identify which BT modem is connected to the PC (squawk feature.) HARTCommDTM software from CodeWrights allows use of the BT modem with FTD frame applications.

## Features and Benefits

HART Registered with HCF = fully HART compliant for communication reliability

- Hardware for wireless communication between PC host and any HART field device
- HART software compatibility – works with all HART compliant HART PC software applications
- Enables device management and troubleshooting of HART field devices
- Powered by replaceable 3x AAA alkaline batteries - battery life approximately 20 hours.
- ATEX and IS compliant for use inside hazardous areas
- Safety approvals from FM, ATEX; FCC, CE and RoHS compliant
- High power, high speed **Bluetooth** for 100 meter open air range – use PC host outside hazardous area
- Adaptive frequency hopping to reduce RF interference
- Intelligent / adaptive power management to conserve battery power
- 



1600 Enterprise Parkway Twinsburg, OH 44087  
 Phone: 330-486-0056  
 Fax: 330-963-5827

Sales : [sales@mactekcorp.com](mailto:sales@mactekcorp.com)  
 Support : [support@mactekcorp.com](mailto:support@mactekcorp.com)

Uses Windows **Bluetooth** Serial Port Profile (SPP virtual COM port) for simple pairing of PC host and BT modem

- HART software compatibility – works with all HART compliant PC HART applications
- HARTCommDTM software to support use with FDT frame applications
- VIATORCheckBT™ software to test connections and configure BT modem
- High quality 18" leads with MiniGrabber test clips that naturally avoid tangling
- User friendly on-off push button power switch – no costly operator training required
- LED feedback of power-on state and LED heartbeat showing HART traffic

## Technical Data

<b>Host System</b>	
Platform	Any PC, PDA, Laptop or other computer with <b>Bluetooth</b> support
Operating System	Windows, Windows Mobile, or any OS that supports <b>Bluetooth</b> COM port
Application	Any HART compatible communication application
<b>RF</b>	
<b>Bluetooth</b>	Version 2.0 EDR ( <b>Bluetooth</b> 2.0 Class 1)
Range	100 meters (open air)
Operating Frequency	2.4GHz (2402 – 2480 MHz), 79 channels
RF Output Power	18dBm ( <b>Bluetooth</b> 2.0 Class 1)
Antenna	Integrated Omni-Directional
<b>Electrical</b>	
Batteries (Note 1)	Accepts 3 – AAA, 1.5VDC, alkaline cells, type IEC-LR03
Battery Life (per charge)	Approximately 20 hours continuous usage.
Output Level	Fully HART compliant trapezoidal wave @ 1200/2200 Hz
<b>Environmental</b>	
Operating	-20°C to 50°C (-4°F to 122°F), 0% to 95% relative humidity non-condensing
Storage	-20°C to 35°C (-4°F to 95°F), 0% to 95% relative humidity non-condensing
<b>Enclosure</b>	
Dimension, Material, IP Rating	88mm x 42mm x 19mm, Conductive ABS, Enclosure rating: IP20
<b>Electrical Connections</b>	
HART I/O Interface Cable	.5m length, 20AWG stranded, termination BLUE mini-grabbers



1600 Enterprise Parkway Twinsburg, OH 44087  
 Phone: 330-486-0056  
 Fax: 330-963-5827

Sales : [sales@mactekcorp.com](mailto:sales@mactekcorp.com)  
 Support : [support@mactekcorp.com](mailto:support@mactekcorp.com)

<b>Certifications</b>	
Directive EMC 2004/108/EC	CE approved for emissions and immunity, EN 61326-1
<b>BLUETOOTH</b> modular approvals	Contains FCC ID: TJ9RN41-1 and IC ID: 6514A-RN-411 CE 0681
Directive (RoHS) 2002/95/EC	Restricted materials not used
<b>European Approvals</b>	
ATEX	II 1G Ex ia IIC T4 -20°C ≤ ta ≤ +50°C
<b>United States &amp; Canadian Approvals</b>	
FM Approvals	
Intrinsic Safety (Division)	Class I, Division 1, Group A,B,C,D (Gas), T4 -20°C ≤ ta ≤ +50°C
Intrinsic Safety (Zone)	AEx ia IIC T4 -20°C ≤ ta ≤ +50°C
Non-Incendive	Class I, Division 2, Group A,B,C,D (Gas ),T4 -20°C ≤ ta ≤ +50°C

Note 1: Intrinsic Safety Certifications are valid only with approved alkaline batteries installed.

Approved battery: Energizer EN92

HART® is a registered trademark of the HART Communication Foundation. MACTek®, VIATOR®, and VIATORCheckBT™ is a trademark of the Pepperl+Fuchs MACTek Inc, The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.



1600 Enterprise Parkway Twinsburg, OH 44087  
 Phone: 330-486-0056  
 Fax: 330-963-5827

Sales : [sales@mactekcorp.com](mailto:sales@mactekcorp.com)  
 Support : [support@mactekcorp.com](mailto:support@mactekcorp.com)